ID NO: 010	COSHH ASSESSMENT RECORD DOWSE
SUBSTANCE	HYDRATED LIME
IDENTIFICATION	Free flowing, very fine white powder.
PROCESS/OR USE	Use as a constituent of mortar.
RISKS TO HEALTH	Irritating to eyes and skin. Risk of serious damage to eyes. May cause burns in the presence of moisture.
CAN THE EXPOSURE	BE ELIMINATED NO Details specified below
	EYES: Wash immediately with copious amounts of water. SKIN: Wash thoroughly with soapy water. INHALATION: Remove to fresh air. INGESTION: Wash mouth out with water and give milk to drink.
COPY	MUST BE SENT WITH INJURED PARTY TO HOSPITAL
	FIRE FIGHTING MEASURES (Tick Box)
DANGEROUS FOR THE ENVIRONMENT	Wear correct PPE avoid skin and eye contact and avoid breathing in dust. Contained spilled product with sand or earth or other absorbent material. Prevent spills entering waterways and drains. Notify Environment Agency or other bodies if spills enter waterways or drains.
	EXPOSURE LIMITS (EH 40)
	Time Exposed: Number of People Exposed:
COSK	Workplace Exposure Limit (WEL) Long Term Exposure Limit - 8 Hour TWA NA ppm Inhalable 10 Respirable 4 mg.m ⁻³
	Short Term Exposure Limit - 15 Minute NA ppm NA mg.m ⁻³
PPE (Tick Box)	
CONTROL MEASURES	Advise all persons involved in the use of hydrated lime on the inherent dangers of cement in the form of site start up briefing. Thorough site supervision to be maintained to ensure that PPE is worn without exemption.
Assessment By: Risk	Advisor Date: Apr 2005 Review Date: Apr 2010 (maximum 5 years)
·	