

















ID NO: 004		COSHH ASSESSMENT RECORD		DOWSE			
SUBSTANCE		PROPANE					
IDENTIFICATION		Liquefied gas under pressure contained in a red cylinder.					
PROCESS/OR USE		Welding, burning and industrial heating.					
RISKS TO HEALTH		In high concentrations, may cause asphyxiation. EXTREMEY FLAMMABLE.					
CAN THE EXPOSURE BE ELIMINATED				NO		Details specified below	
		FIRST AID MEASURES EYES: Flush with water for 15 minutes, apply a sterile dressing and seek medical advice as soon as possible. INHALATION: Remove victim to uncontaminated area wearing self contained breathing apparatus, keep victim warm and rested, call a Doctor, apply CPR if breathing stopped.					
COPY MUST BE SENT WITH INJURED PARTY TO HOSPITAL							
		FIRE FIGHTING MEASURES (Tick Box)  <input checked="" type="checkbox"/>  <input checked="" type="checkbox"/>  <input checked="" type="checkbox"/>  <input checked="" type="checkbox"/>					
		SPILLAGE & ENVIRONMENTAL DETAILS Wear self-contained breathing apparatus when entering contaminated area. Ensure adequate ventilation. Eliminate ignition sources. Try to stop release, prevent from entering sewers, basements and work pits.					
		EXPOSURE LIMITS (EH 40) Time Exposed: _____ Number of People Exposed: _____ <hr/> Workplace Exposure Limit (WEL) Long Term Exposure Limit - 8 Hour TWA NA ppm NA mg.m ⁻³ Short Term Exposure Limit - 15 Minute NA ppm NA mg.m ⁻³					
PPE (Tick Box)		 <input checked="" type="checkbox"/>  <input checked="" type="checkbox"/>  <input type="checkbox"/>  <input checked="" type="checkbox"/>  <input type="checkbox"/>  <input checked="" type="checkbox"/>  <input checked="" type="checkbox"/>					
CONTROL MEASURES		Only authorised persons to be allowed to weld or burn. Only authorised persons to change heating appliance propane cylinders. Thorough site supervision to ensure the correct PPE is worn. Keep welding and burning equipment secure. No smoking allowed while handling product.				Site Agent Operative	
Assessment By: Risk Advisor		Date: Apr 2005		Review Date: Apr 2010		(maximum 5 years)	

